

## CALIPERS

## PADS

## ROTORS

## HATS

## HARDWARE

SHORT TRACK & ROAD COURSE

**CAR1249Z04TESLL/RL (ENP)**


1.63"/1.37"/1.19" (41.3/34.9/30.2mm) Pistons  
1.65" (42mm) Thick Rotor, Caliper Weight 6.3 lbs



bracket **PBC5006 - BKC4412X104**  
seal kit (axle set) **PHK4002 - CSK303541E751X**

1.63" (41.3mm) titanium piston  
1.37" (34.9mm) titanium piston  
1.19" (30.2mm) titanium piston  
bleed screw kit with o-rings (axle set) **PTH4135X110E**  
**PTH3535X110E**  
**PTH3035X110E**  
**PHK4044 - FSK3430X689**

**Raybestos - R601**  
1.18" (30mm)



**PAD SHAPES**  
Raybestos - ST\*\*R601.30  
PFC - 7807.30  
Pagid / Mintex - 2016L  
Project Mu - F5820

**DIV4240X001CL/R**  
12.91" x 1.65" (328mm X 42mm)  
70 "Turbulator" Vane, 21.5 lbs  
12 X 7.2" Bolt Circle

**DIV4229X046CL/R**  
12.91" x 1.57" (328mm X 40mm)  
56 "Turbulator" Vane, 20.2 lbs  
12 X 7.2" Bolt Circle

**BAD2129X1457P**  
1.419" (36.0mm) Offset

**BAD2129X1456P**  
1.552" (39.4mm) Offset

**PRH3007**  
**BAD2129X924P**  
1.68" (42.6mm) Offset

**PRH3004**  
**BAD2129X908P**  
1.81" (46.1mm) Offset

**PRH3003**  
**BAD2129X907P**  
1.94" (49.4mm) Offset

**PRH3012**  
**BAD2129X977P**  
2.07" (52.6mm) Offset

**PRH3005**  
**BAD2129X918P**  
2.09" (53.0mm) Offset

**BAD2129X1429P**  
2.195" (55.7mm) Offset

**BAD2129X1213P**  
2.32" (59.0mm) Offset

401ME Standard Bobbins:  
**PHK4075**  
**BSD3430X401ME.24**

656ME High Profile Bobbins:  
**PHK4039**  
**BSD3430X656ME.24**

Bolts:  
**PHK4040**  
**BSS4474X641.24**

Hex Nuts:  
**PHK4041**  
**NST0080X792.24**  
Nut Torque= 156 in-lbs

12 Each Per Hat  
(24 Units Per Kit)

FRONT INTERMEDIATE

**CAR1149AN03TESLL/RL(ENP)**

1.63"/1.25"/1.125" (41.3/31.8/28.6mm) Pistons  
1.42 - 1.57" (36 - 40mm) Thick Rotors,  
Caliper Weight 5.5 lbs.



bracket **PBC5006 - BKC4412X104**  
seal kit (axle set) **PHK4024 - CSK293241E751X**

1.63" (41.3mm) titanium piston  
1.25" (31.8mm) titanium piston  
1.125" (28.6mm) titanium piston  
bleed screw kit with o-rings (axle set) **PTH4138X110E**  
**PTH3238X110E**  
**PTH2938X110E**  
**PHK4044 - FSK3430X689**

**retraction components**  
pad retraction kit (axle set) **PHK4050 - PRK2941X110**  
**CSK293241E752**

lowest retraction seal kit (axle set) **PHK4032**  
middle retraction seal kit (axle set) **CSK293241E755**

**Raybestos - R2602**  
1.14" (29 mm)



**Pad Shapes**  
Raybestos - ST\*\*R2602.29  
Pagid / Mintex - 1850  
PFC - 7790  
Project Mu - F1090

**DIV4240X032CL/R (unbedded)**  
12.91" x 1.57" (328mm X 40mm)  
70 "Turbulator" Vane, 18.6 lbs

**PR2069L/R (unbedded)**  
**DIV4212X031CL/R**  
12.91" x 1.50" (328mm X 38mm)  
72 Vane, 17.2 lbs

**PR2067L/R (unbedded)**  
**DIV4212X030CL/R**  
12.91" x 1.42" (328mm X 36mm)  
72 Vane, 15.6 lbs  
12 X 7.79" Bolt Circle

**BAD2129X1458P**  
1.517"(38.53mm) Offset

**PRH3017**  
**BAD2129X1187P**  
1.667"(42.35mm) Offset

**PRH3016**  
**BAD2129X1310P**  
1.79" (45.53 mm) Offset

**PRH3010**  
**BAD2129X993P**  
1.87" (47.5 mm) Offset

**PRH3009**  
**BAD2129X988P**  
1.917" (48.7 mm) Offset

**PRH3008**  
**BAD2129X987P**  
2.169" (55.1 mm) Offset

401ME Standard Bobbins:  
**PHK4075**  
**BSD3430X401ME.24**


656ME High Profile Bobbins:  
**PHK4039**  
**BSD3430X656ME.24**

Bolts:  
**PHK4040**  
**BSS4474X641.24**

Hex Nuts:  
**NST0080X792.24**  
Nut Torque= 156 in-lbs

12 Each Per Hat  
(24 Units Per Kit)

**Raybestos - R2600**  
1.14" (29 mm)



**Pad Shapes**  
Raybestos - ST\*\*R2600.29  
Pagid / Mintex - 1852  
PFC - 7793

**PR2038L/R (unbedded)**  
**DIV4212X027CL/R**  
12.72" x 1.54" (323mm X 39mm)  
72 Vane, 16.7 lbs

**PR2039L/R (unbedded)**  
**PR2053L/R (PFC01 bedded)**  
**DIV4212X028CL/R**  
12.72" x 1.44" (323mm X 36.5mm)  
72 Vane, 14.9 lbs

**PRH3015**  
**BAD2129X1297P**  
2.055" (52.2mm) Offset

**BAD2129X1458P**  
1.517"(38.53mm) Offset

**PRH3017**  
**BAD2129X1187P**  
1.667"(42.35mm) Offset

**PRH3016**  
**BAD2129X1310P**  
1.79" (45.53 mm) Offset

**PRH3010**  
**BAD2129X993P**  
1.87" (47.5 mm) Offset

**PRH3009**  
**BAD2129X988P**  
1.917" (48.7 mm) Offset

**PRH3008**  
**BAD2129X987P**  
2.169" (55.1 mm) Offset

**PR2045L/R (unbedded)**  
**DIV2235X585CL/R**  
12.72" x 1.26" (323mm X 32mm)  
48 Vane, 13.4 lbs  
12 X 8.0" Bolt Circle  
\*Calipers need to be fitted with SSC4411X125 pad supports and 0.157" (4mm) thick inserts

**BAD2129X1457P**  
1.419" (36.0mm) Offset

**BAD2129X1456P**  
1.552" (39.4mm) Offset

**PRH3007**  
**BAD2129X924P**  
1.68" (42.6mm) Offset

**PRH3004**  
**BAD2129X908P**  
1.81" (46.1mm) Offset

**PRH3003**  
**BAD2129X907P**  
1.94" (49.4mm) Offset

**PRH3012**  
**BAD2129X977P**  
2.07" (52.6mm) Offset

**PRH3005**  
**BAD2129X918P**  
2.09" (53.0mm) Offset

**BAD2129X1429P**  
2.195" (55.7mm) Offset

**BAD2129X1213P**  
2.32" (59.0mm) Offset

401PE Low Float Bobbins:  
**PHK4076**  
**BSD3430X401PE.24**

401ME Standard Bobbins:  
**PHK4075**  
**BSD3430X401ME.24**

656ME High Profile Bobbins:  
**PHK4039**  
**BSD3430X656ME.24**

Bolts:  
**PHK4040**  
**BSS4474X641.24**

Hex Nuts:  
**PHK4041**  
**NST0080X792.24**  
Nut Torque= 156 in-lbs

12 Each Per Hat  
(24 Units Per Kit)

**CAR2349H15ASLL/RL**

1.63"/1.50" (41.3/38.1mm) Aluminum Pistons  
1.0" (25.4mm) Thick Rotor  
Caliper Weight 4.3 lbs.

**CAR2349H15ASLL/RL Ti**

1.63"/1.50" (41.3/38.1mm) Titanium Pistons  
1.26" (32mm) Thick Rotor,  
Caliper Weight 4.3 lbs.




seal kit (axle set) **PHK4004 - CSK3841E751X**

1.63" (41.3mm) standard aluminum piston for 1" rotor **PAH4132X101**  
1.50" (38.1mm) standard aluminum piston for 1" rotor **PAH3832X101**  
1.63" (41.3mm) titanium piston for 1.26" rotor **PTH4130X110E**  
1.50" (38.1mm) titanium piston for 1.26" rotor **PTH3830X110E**  
bleed screw kit with o-rings (axle set) **PHK4044 - FSK3430X689**

**retraction components**  
pad retraction kit (aluminum pistons, axle set) **PHK4068 - PRK3841X101**  
**CSK3841E752**

lowest retraction seal (axle set) **PHK4030**  
middle retraction seal kit (axle set) **CSK3841E755**  
high retraction seal kit (axle set) **PHK4077 - CSK3841E7575X**

**Raybestos - R2001**  
0.79" (20mm)



**PAD SHAPES**  
Raybestos - ST\*\*DR2001.20

**PR2041L/R (unbedded)**  
**DIV2150X086CL/R**  
12" x 1.0" (305mm X 25.4mm)  
36 Vane, 10.3 lbs  
12 X 7.795" Bolt Circle

**PR2032L/R (unbedded)**  
**DIV2213X529CL/R**  
12" x 1.0" (305mm X 25.4mm)  
72 Vane, 9.4 lbs  
12 X 7.795" Bolt Circle

**BAD2129X1457P**  
1.419" (36.0mm) Offset

**BAD2129X1456P**  
1.552" (39.4mm) Offset

**PRH3007**  
**BAD2129X924P**  
1.68" (42.6mm) Offset

**PRH3004**  
**BAD2129X908P**  
1.81" (46.1mm) Offset

**PRH3003**  
**BAD2129X907P**  
1.94" (49.4mm) Offset


**PRH3012**  
**BAD2129X977P**  
2.07" (52.6mm) Offset

**PRH3005**  
**BAD2129X918P**  
2.09" (53.0mm) Offset

**BAD2129X1429P**  
2.195" (55.7mm) Offset

**BAD2129X1213P**  
2.32" (59.0mm) Offset

**Raybestos - R2002**  
0.79" (20mm)



**PAD SHAPES**  
Raybestos - ST\*\*DR2002.20  
PFC - 7700  
Project Mu - F1070

**DIV2235X636CL/R**  
12" x 1.26" (305mm X 32mm)  
48 Vane, 12.5 lbs  
12 X 7.2" Bolt Circle